| ENGINEER'S ESTIMATE | OPENING DATE | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| $50,000.00 | TEUSDAY, JANUARY 11, 2022 @ 2:00 P.M. | | | | | | | | | | | |
| CONTRACT NUMBER AND TITLE | | | Custom Bandag, Inc. | | Advance Tire, Inc. | | | | | | | |
| SW-EQUIP-08-22 Furnish Deliver and Intsall Eight (8) new 23.5R25 soft riding solid rubber tires on two (2) a John Deer 644K Front End Loaders at the Transfer Station | | | | | | | | | | | | |
| ITEM | DESCRIPTION | QUANTITY | UNIT PRICE | EXT. PRICE | UNIT PRICE | EXT. PRICE | UNIT PRICE | EXT. PRICE | UNIT PRICE | EXT. PRICE | UNIT PRICE | EXT. PRICE |
| 1 | FURNISH, DELIVER AND INSTALL NEW 23.5R25 SOFT RIDING SOLID RUBBER TIRES, AS SPECIFIED | 8 | 4,900.00 | 39,200.00 | 5,395.00 | 43,160.00 | | | | | | |
| | TOTAL AMOUNT BID | | | 39,200.00 | | 43,160.00 | | | | | | |
| | | Required | Provided | | Provided | | Provided | | Provided | | Provided | |
| | BIDDER'S CHECKLIST | x | yes | | yes | | | | | | | |
| | STATEMENT OF OWNERSHIP DISCLOSURE | x | yes | | yes | | | | | | | |
| | NON-COLLUSION AFFIDAVIT | x | yes | | yes | | | | | | | |
| | SUBMITTALS AS PER ITEM E, PAGE IV-2 | x | no | reject | yes | | | | | | | |
| | PROPOSAL FORM(S) | x | yes | | yes | | | | | | | |
| | ADDENDA ACKNOWLEDGEMENT | x | yes | | yes | | | | | | | |
| | DISCLOSURE OF INVESTMENT ACTIVITIES IN IRAN | | yes | | no | | | | | | | |
| | N.J. BUSINESS REGISTRATION CERTIFICATE | | yes | valid | no | | | | | | | |
| | IRS FORM W-9 | | yes | | no | | | | | | | |
| | INSURANCE CERTIFICATE(S) | | yes | CMCMUA named as certificate holder | no | | | | | | | |
| | MANDATORY AFFIRMATIVE ACTION | | yes | 15-Oct-2024 | no | | | | | | | |
| | | | | | | | | | | | | |
| IV-2 | E. Submittals The successful Bidder shall provide the following submittals to the CMCMUA for review and approval. Submittals shall include, but not be limited to, two (2) copies of each of the following: Detailed drawings of the solid rubber tire showing the dimensions, locations and size of the aperture holes, the tread pattern, tread depth and the thickness of the wearable rubber. | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |